



QXJY.EX28343 - Centrifugal Fire Pumps, Split Case

Centrifugal Fire Pumps, Split Case

[See General Information for Centrifugal Fire Pumps, Split Case](#)

FIREGUARD GLOBAL LTD

EX28343

3 CHURCH ST
 KIDDERMINSTER
 WORCESTERSHIRE, DY10 2AD UNITED KINGDOM

Fire pumps, single stage

Rated Capacity (gpm)	Size (in.)	Model Dsg	Rated Net Pressure Range (psi)	Approx Speed (rpm)	Max Working Pressure (psi)
2000	10x8	SCF250-200-350	123-239	2980	362
2500	10x8	SCF250-200-350	114-227	2980	362

Fire pumps, single stage

Rated Capacity (gpm)	Size (in.)	Model Dsg	Rated Net Pressure Range (psi)	Approx Speed (rpm)	Max Working Pressure (psi)
300	5x3	ASF5-3X10	83-136	2950	280
300	5x3	ASF5-3X10	120-196	3550	280
400	5x3	ASF5-3X10	82-135	2950	280
400	5x3	ASF5-3X10	120-196	3550	280
450	5x3	ASF5-3X10	80-134	2950	280
450	5x3	ASF5-3X10	119-196	3550	280
500	5x3	ASF5-3X10	79-133	2950	280
500	5x3	ASF5-3X10	118 - 195	3550	280
750	5x3	ASF5-3X10	108 - 120	2950	280
750	5x3	ASF5-3X10	105-185	3550	280
750	8x6	ASF8-6X17	272-367	2950	460

Rated Capacity (gpm)	Size (in.)	Model Dsg	No. of Stages	Rated Net Pressure Range (psi)	Approx Speed (rpm)	Max Working Pressure (psi)
750	8x6	FGSF8-6X18x2	2	263-361	1800	450
750	8x6	ANCSF8-6X18x2	2	263-361	1800	450
1000	8x6	FGSF8-6X18x2	2	253-354	1800	450
1000	8x6	ANCSF8-6X18x2	2	253-354	1800	450
1250	8x6	FGSF8-6X18x2	2	236-342	1800	450
1250	8x6	ANCSF8-6X18x2	2	236-342	1800	450
1500	8x6	FGSF8-6X18x2	2	324	1800	450
1500	8x6	ANCSF8-6X18x2	2	324	1800	450

Trademark and/or Tradename:  ,  , "FIREGUARD GLOBAL"

Last Updated on 2020-05-21

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"



QWZU.EX28373 - Centrifugal Fire Pumps, End Suction

Centrifugal Fire Pumps, End Suction

See General Information for Centrifugal Fire Pumps, End Suction

FIREGUARD GLOBAL LTD



EX28373

3 CHURCH ST
 KIDDERMINSTER
 WORCESTERSHIRE, DY10 2AD UNITED KINGDOM

Rated Capacity GPM	Size In.	Model Dsg	Rated Net Pressure Range psi	Approx Speed RPM	Max Working Pressure psi
200	2-1/2x2	FGEF 50/26	105-140	2980	232
200	2-1/2x2	ANCEF 50/26	105-140	2980	232
250	2-1/2x2	FGEF 50/26	99-136	2980	232
250	2-1/2x2	ANCEF 50/26	99-136	2980	232
250	3x2-1/2	FGEF 65/26	119-147	2980	239
250	3x2-1/2	ANCEF 65/26	119-147	2980	239
300	3x2-1/2	FGEF 65/26	119-147	2980	239
300	3x2-1/2	ANCEF 65/26	119-147	2980	239
400	3x2-1/2	FGEF 65/26	119-141	2980	239
400	3x2-1/2	ANCEF 65/26	119-141	2980	239
450	3x2-1/2	FGEF 65/26	114-138	2980	239
450	3x2-1/2	ANCEF 65/26	114-138	2980	239
500	3x2-1/2	FGEF 65/26	111-135	2980	239
500	3x2-1/2	ANCEF 65/26	111-135	2980	239
500	4x3	FGEF 80/26	116-138	2980	232
500	4x3	ANCEF 80/26	116-138	2980	232
750	4x3	FGEF 80/26	105-132	2980	232
750	4x3	ANCEF 80/26	105-132	2980	232

200	2-1/2x2	FGEF 50/20	72-99	2980	232
200	2-1/2x2	ANCEF 50/20	72-99	2980	232
250	2-1/2x2	FGEF 50/20	69-99	2980	232
250	2-1/2x2	ANCEF 50/20	69-99	2980	232
200	2-1/2x2	FGEF 50/20	102-142	3550	232
200	2-1/2x2	ANCEF 50/20	102-142	3550	232
250	2-1/2x2	FGEF 50/20	101-141	3550	232
250	2-1/2x2	ANCEF 50/20	101-141	3550	232
250	3x2-1/2	FGEF 65/20	86-107	2980	232
250	3x2-1/2	ANCEF 65/20	86-107	2980	232
300	3x2-1/2	FGEF 65/20	86-107	2980	232
300	3x2-1/2	ANCEF 65/20	86-107	2980	232
400	3x2-1/2	FGEF 65/20	83-104	2980	232
400	3x2-1/2	ANCEF 65/20	83-104	2980	232
450	3x2-1/2	FGEF 65/20	80-102	2980	232
450	3x2-1/2	ANCEF 65/20	80-102	2980	232
500	3x2-1/2	FGEF 65/20	77-99	2980	232
500	3x2-1/2	ANCEF 65/20	77-99	2980	232
250	3x2-1/2	FGEF 65/20	113-152	3550	232
500	3x2-1/2	ANCEF 65/20	77-99	2980	232
300	3x2-1/2	FGEF 65/20	112-152	3550	232
300	3x2-1/2	ANCEF 65/20	112-152	3550	232
400	3x2-1/2	FGEF 65/20	108-150	3550	232
400	3x2-1/2	ANCEF 65/20	108-150	3550	232
450	3x2-1/2	FGEF 65/20	105-148	3550	232
450	3x2-1/2	ANCEF 65/20	105-148	3550	232
500	3x2-1/2	FGEF 65/20	101-145	3550	232
500	3x2-1/2	ANCEF 65/20	101-145	3550	232
500	4x3	FGEF 80/20	90-100	2980	232

500	4x3	ANCEF 80/20	90-100	2980	232
750	4x3	FGEF 80/20	87-98	2980	232
750	4x3	ANCEF 80/20	87-98	2980	232
500	4x3	FGEF 80/20	129-142	3550	232
500	4x3	ANCEF 80/20	129-142	3550	232
750	4x3	FGEF 80/20	127-142	3550	232
750	4x3	ANCEF 80/20	127-142	3550	232
50	2-1/2x1-1/2	FGEF 40/20	76-111	2980	232
50	2-1/2x1-1/2	ANCEF 40/20	76-111	2980	232
100	2-1/2x1-1/2	FGEF 40/20	72-109	2980	232
100	2-1/2x1-1/2	ANCEF 40/20	72-109	2980	232
50	2-1/2x1-1/2	FGEF 40/20	108-157	3550	232
50	2-1/2x1-1/2	ANCEF 40/20	108-157	3550	232
100	2-1/2x1-1/2	FGEF 40/20	105-157	3550	232
100	2-1/2x1-1/2	ANCEF 40/20	105-157	3550	232
100	2-1/2x1-1/2	FGEF 40/26	100-138	2980	232
100	2-1/2x1-1/2	ANCEF 40/26	100-138	2980	232

Trademark and/or Tradename:  , "FIREGUARD", "FIREGUARD GLOBAL", 

Last Updated on 2020-05-21

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2020 UL LLC"